



FibreTEKS®

FibreTEKS®

Buildex® first again with Teks screw specifically designed and manufactured for fixing non compressed Fibre Cement sheeting 6 – 12mm to steel battens 0.9 – 4.0mm.

Featuring the latest Tek® drill point and Phillips drive to reduce the need for pre-drilling, and a lip feature designed to prevent over drilling and allows for a flush finish.

Patented lip feature, ensures the screw will stop as soon as it makes contact with the surface of the board. Prevents overdriving but allows for minimum embedment and a flush finish.



Product Features



Buildex® Warranty



E-coat®


How To Use

1. Can be installed using either a battery powered or mains powered screw gun.
2. Recommended that a nose cone should be used with screw gun.
3. Use a Buildex® No. 2 Phillips Recess drive bit.

Countersunk Ribbed Head - FibreTek®

Non Compressed Fibre Cement Sheeting 6 – 12mm to steel battens from 0.9 – 4mm.



Gauge	T.P.I	Length	Pack / Carton Qty	Pallet Qty	Part Number	Product Features
4.8mm / 10g	16	25	500 / 3	108,000	6-311-0676-6EC	 

Countersunk Ribbed Head - FibreTek® Collated (Coming Soon)



Gauge	T.P.I	Length	Pack / Carton Qty	Pallet Qty	Part Number	Product Features
4.8mm / 10g	16	25	1000 / 8	180,000	6-318-0676-7EC	 

Technical Specifications					
Pullout data into G450 steel (Kilo Newtons)					
1.0mm G500	1.2mm G500	1.5mm G450	1.9mm G450	2.4mm G450	3.2mm G450
2.8	3.5	4.3	5.8	8.3	9.5
Pullout data into G250/G300 steel (Kilo Newtons)					
1.0mm G300	1.2mm G300	1.5mm G250	1.9mm G350	2.4mm G250	3.2mm G250
1.8	2.5	3.4	4.9	7.0	8.4
Pullout data into RONDO steel (Kilo Newtons)					
0.8mm Rondo	1.2mm Rondo				
1.0	1.9				
Pullover Load (Kilo Newtons)					
6mm Sheeting	7.5mm Sheeting	9mm Sheeting	112mm Sheeting		
0.65	1.04	1.40	2.0		
Results may vary subject to types of sheeting used.					
Mechanical Properties					
Shear (kN), Single Shear	Tensile (kN) Axial Tensile	Torsional (Nm) Torsional Strength			
6.8	11.9	8.4			
Corrosion Test Result Summary...					
Test	Conditions	Requirements			E-coat
Kesternich ASTM G-87	15 cycles	<15% red rust on significant surface areas			PASS
Salt Spray ASTM B117-03	1000 hours	0% red rust on significant surface areas			PASS